

Allmand

Port-A-Lite™

PAL 1250 and PAL 2500



Night-Lite Pro™

Maxi-Lite®

TLB™

Port-A-Lite™

Eclipse®

Maxi-Heat®

- 1250 watt lamps are equipped with exclusive SHO lamp fixture for brighter, cleaner light
- Compact design provides easy storage and transport
- Wheels feature heavy-duty ball bearings for long life and easy positioning

Strong Past. Dynamic Future.

Reliability, performance,
and integrity since 1938



PORT-A-LITE
PAL 1250W2 AND
PAL 2500W4

Allmand™

SPECIFICATIONS



PAL 1250W2

One 1250 Watt SHO fixture, 120V / 11A
Fixture storage on base
Light adjusts in all directions without tools
Maximum adjustable height to 10 ft.
Packaged in three boxes, 115 lbs



PAL 2500W4

Two 1250 Watt SHO fixtures, 125V / 11A each
Fixture storage on base
Heavy-duty generator cart
Front caster wheels with brakes
10 inch ball-bearing rear wheels
Winch-up tower
Maximum adjustable height to 12 ft.
Packaged in four boxes, 225 lbs.

IMPORTANT NOTES

Metal Halide floodlights require a four to five minute warm-up time to reach full brightness and a cool-down time of up to 15 minutes before re-lighting.

When using any metal halide floodlight with portable generators, it is important to have the lights OFF when starting and before stopping the generator.



VALUE-ADDED FEATURES

Durable SHO parallel lamp fixtures produce up to 50 percent more lumens per fixture than competitive models.

Caster Brakes on PAL 2500W4 enhances safety.

Winch-up tower on PAL 2500W4 for ease of set-up and infinite positioning capabilities.

Utilizing power from one 120 Volt outlet, the Allmand SHO parallel lamp fixture, equipped with a 1250 Watt metal halide lamp, illuminates five times more area than a 1000 Watt quartz light.

Wheels feature heavy-duty ball-bearings for long life and ease of positioning.

Sturdy welded steel frame with durable plated inner towers extends product life.

Insulated lamp supports isolate lamp from damaging vibration, extending average lamp life.

Frosted lens diffuses light to comfortably reduce glare without affecting light coverage.

Worldwide and domestic voltages available on request.

Allmand

REV D

ALLMAND BROS. INC.
1502 West 4th Ave.
Holdrege, NE 68949
PH. 800.562.1373 Fax 308.995.5887
www.allmand.com

*Reliability, performance,
and integrity since 1938*

