



Maxi-PowerTM

Mobile Generator

SOUND ATTENUATED

HEAVY-DUTY, OVER-SIZED ALTERNATOR

HIGH CAPACITY, COLD START BATTERY

AUTOMATIC VOLTAGE REGULATOR (AVR)

120 VOLT GFCI RECEPTACLES ALWAYS
ENERGIZED WHILE RUNNING

ADJUSTABLE COUPLER CHANNEL

FREQUENCY SWITCH TO RUN
50 Hz OR 60 Hz



SINCE 1938

Reliability, Performance and Integrity.

Maxi-Power™

Mobile Generator

Maximize the power of your jobsite with the Maxi-Power™ Mobile Generator. This generator comes equipped with a heavy-duty, oversized alternator equipped for motor starting needs. With a frequency switch for flexibility of jobsite power needs, and 15 inch tires for longer wear and greater towing capabilities, this generator will last and deliver the power you need to get the job done.



KEY FEATURES

- 110% Full Fluid Containment
- Oversized Electrical Lugs
- Large Capacity Fuel Tank¹
- Standard External Fuel Connections
- Standard Programmable Start/Stop for Standby Applications
- Electric Fuel Primer & Air-Bleed (EFPA) Pump
- Hydraulic Surge Brakes Standard
- Lockable Switch / Voltage Selector
- Curbside Fluid Maintenance / Side Fork Pockets (MP25)
- Trailer DOT Compliant 49 CFR
- Trailer Optional
- Warranty Coverage / Product: 2 Years/2,000 Hour Limited Warranty*
- GPS Ready

Model Number	MP25	MP40	MP45	MP65-8B1
Armature Connection	Star with Neutral/Zig/Zag			
Number Of Poles	4 Pole			
Insulation	Class F			
Excitation	Brushless with AVR			
Voltage Regulation Percentage	0.50%			
Power Factor	0.80			
Frequency - Hz (Switchable)	60 (50)			
Standby Power - kVA (kW)	27.5 (22)	39 (31.2)	48.5 (38.8)	67 (53.6)
Prime Power - kVA (kW)	25 (20)	38 (30.4)	45 (36)	63 (50)
Voltage Single Phase (Switchable) (V)	120 / 240 / 277			
Voltage Three Phase (Switchable) (V)	208 / 240 / 416 / 480			
Amperage Single Phase 120 V (A)	60 x 2	91 x 2	108 x 2	152 x 2
Amperage Single Phase 240 V (A)	60	91	108	152
Amperage Three Phase 208 V (A)	65	105	119	167
Amperage Three Phase 240 V (A)	60	91	108	152
Amperage Three Phase 480 V (A)	30	46	54	76
Engine Brand	Isuzu	Kubota	Isuzu	Isuzu
Engine Model	4LE2T	V3300	4LE2X	4JJ1X
EPA Emissions Certified	Tier 4 Final	Interim Tier 4	Tier 4 Final	Tier 3 Flex
Number of Cylinders	4	4	4	4
Output @ Rated Speed (1,800 RPM) - HP	33	47	59	98
Governor Type	Isochronous			
Integral Fuel Tank Capacity (gal)	52	106	106	106
Full Fluid Containment	110%			
Lubricating Oil Capacity gal (L)	2.7 (10.4)	3.4 (13.2)	3.1 (11.7)	4.0 (15.0)
Coolant Capacity gal (L)	2.7 (10.4)	2.9 (11.0)	2.5 (9.5)	2.9 (11.0)
Battery (V)	12	12	12	12
Run Time @ Full Load	31+	40+	36+	28+
Length W/O Trailer (in)	67	82	82	82
Width W/O Trailer (in)	32	39	38	39
Height W/O Trailer (in)	55	61	61	61
Dry Weight (lbs)	1,764	2,555	2,425	2,877
Operating Wet Weight (lbs)	2,161	3,325	3,197	3,660
Sound Level @ 23 ft (NO LOAD) - dBA	< 63	< 61	< 64	< 63
Trailer Length (in)	120	140	140	140
Trailer Width (in)	61	66	66	66
Trailer Height (in)	28	25	26	26
Trailer Weight (lbs)	610	950	950	950
Trailer GVWR (lbs)	3,500	5,750	5,750	5,750

¹Unit runs at full load for 24+ hours. Allmand® has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice. See operator's manual or www.allmand.com website for complete warranty details.

OPTIONS



Camlocks

- Interchangeable electrical connectors that can be used in either single or three phase modes
- Single set of 5 Camlocks



Arctic Package

- 50 W 120 V battery heater pad
- 1,000 W 120 V thermosiphon block heater with thermostat to maintain temperature



Battery Charger (MP25 Only)

- 5 A 120 V with 3 stage charge cycle

Lockable Battery Disconnect (MP25 Only)

Electric Brake on MP65



WHY ALLMAND®

When it comes to managing a jobsite, you want equipment that will not fail you when you need it most. You're looking for trust and reliability. Allmand® brings that to your jobsite, with over 75 years of respected experience. Our focus on Service and Support allows users to get the parts, technical service and support they need. Product innovation has helped us develop state-of-the-art towable jobsite equipment, bringing portable light towers, mobile industrial heaters, portable light stands, portable air compressors and mobile generators for the construction, mining, oil & gas, and rental markets.



Holdrege, Nebraska 68949
P: (800) 562-1373 • F: (308) 995-5887
www.allmand.com

SINCE 1938