### 

# **Night-Lite**E-Series

154,000 TOTAL LUMENS WITH LED FIXTURES22 FT 9 IN ELECTRIC WINCH TOWERMULTIDIRECTION FORK POCKETS



### SINCE 1938

Reliability, Performance and Integrity.

## Night-Lite

As the special event solution, the Night-Lite<sup>™</sup> E-Series is a plug in unit built to be easily deployed across a venue. With multi directional forklift pockets and the ability to withstand 50 mph winds this unit has the durability to be used in many different environments. Performance is key with the Night-Lite<sup>™</sup> E-Series. This unit offers a 154,000 lumens output to light up your space with 4 LED light fixtures, as well as an automatic on/off functionality with a timer and photocell.



### **KEY FEATURES**

- LED Light Fixtures
- Ease of Use Auto On/Off -Timer, Photocell or Manual
- Multidirectional Fork Pockets
- DC Electric Winch
- Reflective Striping
- 359° Fixture Rotation
- 50 mph Operating Wind Speed Rating

### WHY ALLMAND<sup>®</sup>

When it comes to managing a jobsite, you want equipment that will not fail you when you need it most. You're looking for trust and reliability. Allmand' brings that to your jobsite, with over 75 years of respected experience. Our focus on Service and Support allows users to get the parts, technical service and support they need. Product innovation has helped us develop state-of-theart towable jobsite equipment, bringing portable light towers, mobile industrial heaters, portable light stands, portable air compressors and mobile generators for the construction, mining, oil & gas, and rental markets.

Model	Night-Lite <sup>™</sup> E-Series
Light Type	LED
Power Consumption – Per Fixture (W)	320
Number of Fixtures	4
Lumens Per Fixture	38,500
Lumens – Total	154,000
Required Current (4 Lamps) (A)	14
Features	
Tower	<b>Structure</b> – Five section tubular steel design <b>Actuation</b> – Electric winch <b>Tower rotation</b> – Complete tower rotates 359° <b>Guide pads</b> – Polyethylene self lubricating
Frame	Frame - Formed, welded steel frame Multi-directional fork pockets - Ease of transport Tires - Grease seals in raceway, poly on aluminum wheel and a stainless roller bearing
Plug Type	3-Wire Grounded (NEMA 5-15P)
Stabilizers	Four-point design – Four foldable outriggers at corners of unit
Weights & Dimensions	
Tower Maximum Height – ft (m)	22.9 (7.0)
Shipping Weight – Ibs (kg)	720 (326.6)
Length – Transport Position in (mm)	45.0 (1,143)
Width - Transport Position in (mm)	32.0 (813)
Height Tower Lowered – Transport Position in (mm)	88.8 (2,255)
Shipping	Fit 41 units on a 48' truck



Holdrege, Nebraska 68949 P: (800) 562-1373 • F: (308) 995-5887 www.allmand.com

### SINCE 1938