



# Port-A-Lite®

**PAL Single LED / PAL Dual LED**

**38,500 TO 77,000 TOTAL LUMENS**

**10 FT TO 12 FT MAXIMUM  
ADJUSTABLE HEIGHT**



**SINCE 1938**

Reliability, Performance and Integrity.

# Port-A-Lite®

## PAL Single LED / PAL Dual LED

Compact and powerful, the Port-A-Lite® series provides the portable lighting needed to produce the highest quality work in concrete finishing, paving, masonry, roofing, excavation, mining, refineries, quarries, demolition, training sites, and special events. The Dual PAL features a built-in pad for a portable generator so it can be used where utility power is not available. Units available in 120 V 60 Hz and 220 V 50 Hz models.



## KEY FEATURES

- LED Light Fixtures
- Welded Steel Frame
- 10" Diameter Wheels - PAL Single LED
- Caster Brakes - PAL Dual LED
- Winch Actuated Mast - PAL Dual LED
- Platform to Accommodate Portable Generator - PAL Dual LED
- Available option of 220 V 50 Hz Schuko Plug

## WHY ALLMAND®

When it comes to managing a jobsite, you want equipment that will not fail you when you need it most. You're looking for trust and reliability. Allmand® brings that to your jobsite, with over 75 years of respected experience. Our focus on Service and Support allows users to get the parts, technical service and support they need. Product innovation has helped us develop state-of-the-art towable jobsite equipment, bringing portable light towers, mobile industrial heaters, portable light stands, portable air compressors and mobile generators for the construction, mining, oil & gas, and rental markets.

Model	PAL Single LED	PAL Dual LED
Light Type	LED	
Power Consumption - Per Fixture (W)	320	
Number of Fixtures	1	2
Lumens Per Fixture	38,500	38,500
Lumens - Total	38,500	77,000
Required Current (A)	3.5	7
Operating Voltage (V)	120	120
Frequency (Hz)	60	60
<b>Features</b>		
Plug Type	3-Wire Grounded (NEMA 5-15P)	3-Wire Grounded (NEMA 5-15P)
<b>Weights &amp; Dimensions</b>		
Length in (mm)	28.7 (729)	49.4 (1254)
Width in (mm)	24.5 (622)	40.0 (1016)
Height - Mast Lowered ft (m)	6.0 (1.8)	7.6 (2.3)
Height - Mast Raised ft (m)	9.7 (2.9)	11.6 (3.5)
Weight - Shipping lbs (kg)	124 (56.2)	210 (95.3)
Weight - Operating lbs (kg)	111 (50.3)	189 (85.7)

Allmand® has a policy of continuous product improvement and reserves the right to modify its specifications at any time and without prior notice. See operator's manual or [www.allmand.com](http://www.allmand.com) website for complete warranty details.



Holdrege, Nebraska 68949  
P: (800) 562-1373 • F: (308) 995-5887  
[www.allmand.com](http://www.allmand.com)

SINCE 1938