





E-SERIES

Lamps		
Number of Light Fixtures	4 fixtures - Standard	
Led Lamp Type (Dip, Smd, Cob, Other)	Chip On Board (COB)	
Led Color Temperature	5,000 K	
Led Lamp Wattage (Per Lamp)	320 W	
Led Lamp Lumens (Per Lamp)	38,500 lm	
Lamp Position Adjustment (Tool-Less, Method)	LED Lamps - Freely rotating left-right & up-down on nylon washers with spring locking pin to hold up-down position. Light Arms - Freely rotating up to 180 degrees with spring locking pin to hold position.	
Light Tower Mast		
Mast Orientation Options	Vertical Mast	
Vertical Mast Wind Rating (MPH)	50	
Vertical Mast Rotation	355°	
Vertical Maximum Mast Height	22 ft 1 in	
Vertical - Number of Mast Sections	5 tower sections	
Vertical - Mast Construction and Material	Tubular Steel	
Control Detail		
Light Fixture Control	Manual On/Off Ambient Lighting On/Off Timer	
Mast Control	Electric Winch	
Control Display Outputs (Hourmeter, etc.)	Timer Display	
Electrical Detail		
Frequency	60 Hz	
Voltage Requirement	120 VAC	
Maximum Current Draw	14 A	
Power Connection	15 A 120 V 2-Pole 3-Wire Plug (NEMA 5-15P) with weatherproof flip lid	
Lamp Circuit Breaker Type and Amperage	15 A Hydraulic/Magnetic	
Winch Circuit Portection	50 A automatic re-set circuit breaker	
Weights and Dimensions		
Operating Weight	720 lb	
Length - Transport Position	45 in	
Width - Transport Position	32 in	
Height with Tower Lowered - Transport Position	89 in	
Truck Load Shipping Quantities - 48' Flatbed	36 units	
Truck Load Shipping Quantities - 53' Flatbed	41 units	
Container Load Shipping Quantities - 40'	30 units	

Frame Detail		
Frame (Material & Gauge)	Steel - 1/4 inch base plate, 7 ga support, 1-1/2 inch square tube	
Handle (Material & Gauge)	Steel - 2 inch diameter tube x 11 ga	
Outrigger quantity	4 swing-down outriggers with jacks	
Leveling Jack Load Capacity	2,000 lb	
Frame Detail (continued)		
Wheel Size	(4) 5 inch diameter x 2 inch wide caster (2) with cam brake	
Control Box Enclosure (Material & Gauge)	Steel - 10 ga enclosure, 12 ga top cover and 16 ga door and front cover	
Door Hinge Material	Steel screws	
Fork Pockets	2 lateral fork pockets. 2 longitudinal fork pockets 4 x 8 inch opening	
Compliance & Certifications		
National Electric Code (NFPA 70)	Yes	
CSA Listed	No	
Limited Warranty Coverage***		
Frame, Mast, Light Fixtures & Controls	1 year parts and labor 2 years parts only	