

NEW
PRODUCT

NIGHT-LITE™ NL5000

**ROI-DRIVEN SOLUTION
BUILT WITH THE
DURABILITY & PERFORMANCE
YOU DEMAND**

90 HOUR RUNTIME

45 gallon fuel tank keeps your jobsite running efficiently

LOWER RISK DEPLOYMENT

Vertical manual winch tower is deployed from the rear of the unit, keeping the operator out of the way of tower cables

MAXIMIZE FREIGHT COSTS

18 UNITS ON A 48' FLATBED

20 UNITS ON A 53' FLATBED

Rear forklift pockets and lifting ring allow for easy loading and unloading of up to twenty units on a flatbed trailer



EXTERIOR FUEL FILL

Convenient fuel fill neck located on the exterior of the unit provides quick refueling of the unit

EASY FIXTURE ADJUSTMENT

Stepping pad makes rotating the mast and adjusting the fixtures from the ground simple



Allmand™

Brighter. Warmer. Safer.

Reliability, Performance and Integrity Since 1938



NIGHT-LITE™

NL5000

SPECIFICATIONS

Engine <small>liquid-cooled diesel engine operating at 1800 rpm:</small>	Kubota 1005 "T4F" 11.7 hp 8 kW generator <small>*CARB- and EPA-Certified **Prime hp rating provided by engine manufacturer ***Prime generator output provided by Allmand testing</small>	
Starting	12 volt electric; glow plug cold starting system	
Fuel Capacity	45 gallon (170 L) (equipped with fuel level indicator)	
Operating Time	90 hrs without refueling @ 0.5 gph	
Lighting	4-1250 watt SHO-HD metal halide fixtures Initial output of 150,000 lumens per lamp (600,000 total)	
	Genset Protect™ (System to protect the engine and generator from starting and stopping with AC power and lighting systems turned off at startup and shutdown)	
Electrical	Alternator (generator): 60 Hz, 1-phase, capacitor-regulated	
	Ballasts: easily serviceable, removable plug-in assemblies	
	20A 120 VAC duplex GFCI outlet	
	Ground rod	
Tower	25 ft. 6 in. (7.77 m) vertical manual winch tower, rear operation	
	Fixtures are able to be accurately adjusted in retracted position before extending tower	
	359° rotating tower	
Trailer	Formed, welded steel frame	
	Adjustable height combination 2 in. (50 mm) ball, 3 in. (75 mm) pintle towing hitch	
	Foldable tongue	
	Operate unit with externally accessible controls	
	Stop/turn/tail lights	
	Rear forklift pockets and lifting ring	
	Tie down rings	
	Engine fluid containment system	
	18 units on a 48' flatbed trailer 20 units on a 53' flatbed trailer	
	Stabilizers	
Domestic Shipping Weight	Each light fixture: 15 lbs (6.8 kg)	
	Dry: 1,710 lbs (775 kg) Wet: 2,040 lbs (925 kg)	
Dimensions	Height mast lowered: 54.5" (1.38 m)	Height mast raised: 25 ft. 6 in. (7.77 m)
	Length: 81.2" (2.06 m)	Width: 55.5" (1.41 m)
	Outrigger width: 105.5" (2.68 m)	13 in. tires and wheels



1502 West 4th Avenue
Holdrege, Nebraska 68949
P: (800) 562-1373
F: (308) 995-5887
www.allmand.com
Copyright ©2015 Allmand Bros., Inc.

Your Allmand Distributor:

